

Nova Outdoor Digital Signage Kiosk



1

Water & Dust Proof: Robust thermally toughened glass face and mild steel enclosure for protection against the elements and the public. IP65 rated keeps dust and moisture out.

2

Sunlight Readable: The Nova range of digital signage features commercial grade ultra high brightness panels (1500 cd/m²); more than 4 times the brightness of a standard television to allow readability in direct sunlight.

3

Temperature Controlled: Nova digital signage features automatic temperature regulation to allow the panels to operate normally in all weather conditions.

Integrated Media Player

As well as featuring AV inputs, Nova digital signage also features a built-in media player allowing content to be displayed without requiring any additional hardware. Nova digital signage can also be upgraded for network administration, allowing content to be updated from a remote location via LAN, WiFi, or 3G.

Touch Screen Option

For applications that require touch screen interaction, Nova digital signage can be upgraded to feature touch screen functionality.

Specifications

Display Size	47 inch	55 inch
Resolution	1080x1920	
Display Area (mm)	590x1045	680.4x1209.6
Pixel Pitch	0.5415x0.5415	0.21x0.63
Colour	1.06 Billion	1.073 G
Response Time	10ms	4.5ms
Power Consumption (W)	530	580
Net Weight (kg)	160	200
Unit Size (WxHxD) (mm)	810x1800x170	880x1950x180
Enclosure Protection	IP65	
Viewing Angle	178°	
Contrast Ratio	8000:1	
Brightness (cd/m2)	1500	
Input Voltage	AC110~240V (50Hz~60Hz)	
Lifetime (hours)	50,000	
Media Formats	Video (MPG, AVI, MP4) Image (JPG, BMP, PNG)	
AV Signal Inputs	HDMI, VGA	
Internal Flash Memory	4GB	
Accessories	AC Power Cable, Remote Control	
Optional Extras	IR Touch Screen	

