

Nova Outdoor Wall Digital Signage



1

Water & Dust Proof: Robust thermally toughened glass face and mild steel enclosure for protection against the elements and the public. IP65 rated keeps dust and moisture out.

2

Sunlight Readable: The Nova range of digital signage features commercial grade ultra high brightness panels (1500 cd/m²); more than 4 times the brightness of a standard television to allow readability in direct sunlight.

3

Temperature Controlled: Nova digital signage features automatic temperature regulation to allow the panels to operate normally in all weather conditions.

Integrated Media Player

As well as featuring AV inputs, Nova digital signage also features a built-in media player allowing content to be displayed without requiring any additional hardware. Nova digital signage can also be upgraded for network administration, allowing content to be updated from a remote location via LAN, WiFi, or 3G.

Touch Screen Option

For applications that require touch screen interaction, Nova digital signage can be upgraded to feature touch screen functionality.

Specifications

Display Size	32 inch	42 inch	47 inch	55 inch
Resolution	1080x1920			
Display Area (WxH) (mm)	366x702	532x939	591x1047	686x1215
Pixel Pitch	0.36375x0.36375	0.1615x0.4845	0.5415x0.5415	0.21x0.63
Colour	1.06 Billion	16.7 Million	1.06 Billion	1.073 G
Response Time	6ms	9ms	10ms	4.5ms
Power Consumption (W)	190	250	300	350
Net Weight (kg)	35	52	65	80
Unit Size (WxHxD) (mm)	550x970x100	670x1310x133	750x1470x125	810x1600x125
Enclosure Protection	IP65			
Viewing Angle	178°			
Contrast Ratio	8000:1			
Brightness (cd/m2)	1500			
Input Voltage	AC110~240V (50Hz~60Hz)			
Lifetime (hours)	50,000			
Media Formats	Video (MPG, AVI, MP4) Image (JPG, BMP, PNG)			
AV Signal Inputs	HDMI, VGA			
Internal Flash Memory	4GB			
Accessories	AC Power Cable, Remote Control, HDMI Cable, Lockable Wall Mount			
Optional Extras	IR Touch Screen			

